SAFETY DATA SHEET

1. Product and Company Identification

Product Name: Magna Spray FY-7900 (Spray-type fluorescent magnetic powder for

magnetic-particle testing)

Company Name: Denshijiki Industry Co., Ltd. Address: 5-6-20 Ukima, Kita-Ku, Tokyo

Section in Charge: Development department

Telephone: +81-3-5970-8681 FAX: +81-3-5970-8680

Emergency Telephone: Same as the section in charge

Date of Creation: October 29, 2007 Date of Revision: January 21, 2021

Reference Number: SDS15107-05e

Product Code: 15107

Recommended Uses and Restrictions on Use: Magnetic particle testing (Spray)

2. Hazards Identification

GHS Classification

Physical Hazards Aerosols Category 1

Health Hazards Acute toxicity (oral) Classification not possible

Acute toxicity (dermal) Classification not possible Acute toxicity (inhalation: vapors/dust/mist) Classification not possible Skin corrosion/irritation Classification not possible Serious eye damage/eye irritation Classification not possible Respiratory Sensitization Classification not possible Skin sensitization Classification not possible Germ cell mutagenicity Classification not possible Carcinogenicity Classification not possible

Reproductive toxicity/effects on or via

lactation

Reproductive toxicity

Specific target organ toxicity (single Category 3 (Anesthetic effect)

Classification not possible

Classification not possible

exposure)

Specific target organ toxicity (repeated Classification not possible

exposure)

Aspiration hazard Classification not possible
Hazardous to the aquatic environment Classification not possible

Environmental Hazards Hazardous to the aquatic environment

(acute)

Hazardous to the aquatic environment Classification not possible

(chronic)

Hazardous to the ozone layer Classification not possible

GHS Label Elements





Pictograms:

Signal Word: Danger

Hazard Statement: Extremely flammable aerosol

Pressurized container: may burst if heated

May cause drowsiness or dizziness

Precautionary Statement:

Prevention Keep away from ignition sources such as heat, sparks, open flames and hot objects. No

smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Avoid breathing gas, mist, vapors, spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/eye protection/face protection/protective clothing.

Response IF SWALLOWED: Do not induce vomiting.

IF ON SKIN: Wash with plenty of water and soap.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor, if you feel unwell.

Storage Store in a well-ventilated place Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 40°C/104°F.

Disposal Dispose of contents/container at an approved waste disposal plant in accordance with

local/regional/national regulations.

Other hazards not categorized by GHS classification

Contact with liquefied gas may cause frostbite

3. Composition/Information on Ingredients

Substance/Mixture: Mixture

Chemical Name or Common Name	Content (%)	CAS No.
Isoparaffin (Aliphatic hydrocarbon)	65–75	68551-20-2
Ferrosoferric oxide		1317-61-9
Organic fluorescent pigment	< 0.5	Registered
Melamine resin		9003-08-1
Sorbitan Monooleate	< 0.5	1338-43-8
LPG (Liquefied Petroleum Gas)		
Propane	10–30	74-98-6
n-butane, i-butane	5–15	106-97-8,75-28-5

4. First Aid Measures

IF INHALED: : Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor, if you feel unwell.

IF ON SKIN: : Take off contaminated clothing immediately and wash skin with plenty of water

and soap. Take off contaminated clothing and wash it before reuse. If skin

irritation occurs, get medical advice/attention.

IF IN EYES: : Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Rinse for at least 15 minutes, and then

get medical attention.

IF SWALLOWED: : Call a POISON CENTER/doctor, if you feel unwell.

If the product remains in the mouth, rinse thoroughly.

Do NOT induce vomiting.

5. Firefighting Measures

Extinguishing Media : Small fire: Carbon dioxide, powder extinguisher, water sprinkling and foam

extinguisher.

Large fire: Water sprinkling, sprayed water and foam extinguisher

Inappropriate Extinguishing

Media

Straight stream of water

Specific Hazards : May explode if aerosol container is at the scene of a fire.

Extremely flammable and easily ignited by heat, spark and flame. May cause vapor-explosion indoors, outdoors or in a sewage trench.

May generate irritant, poisonous, or corrosive gas in a fire.

Special Firefighting

Procedures

Extremely low flash point: Use water if other extinguishing media are not

effective

Remove containers from the fire area, if it can be done safely.

If not, spray containers and the surrounding area with water to keep them cool. Conduct firefighting activities from the most distant place that allows it to be done effectively using an unmanned hose holder or a nozzle with a monitor. Keep cooling containers with plenty of water even after the fire is extinguished.

Protection of Firefighters : Wear appropriate protective equipment to avoid inhalation of toxic gases.

Fight a fire from upwind.

6. Accidental Release Measures

Personal Precautions,

Protective Equipment and Emergency Procedures

: Operators must wear proper protective gear (refer to 8. Exposure

Controls/Personal Protection) and avoid contact with the eyes and skin, and gas

inhalation.

When leaking (spraying), handle from upwind. Keep the leaking spot facing up. Let the gas spray out completely and then perform the subsequent procedures.

Quickly remove nearby ignition sources, high-temperature objects and

flammables. Evacuate anyone who is downwind and keep everyone out except

authorized persons

Ventilate before entering the restricted area.

Environmental Precautions : Avoid draining to drainage trench, sewage trench, basement or a closed space.

Be careful not to discharge into rivers or anywhere else that would affect the

environment.

Method and Materials for Containment and Cleaning

Up

Use tools whose materials do not generate sparks upon impact or due to static

electricity.

For small leaks, collect the material by absorbing the released material with soil,

sand, or non-combustible material.

For large leaks, put sand around the leakage to keep it from flowing out. Process contaminated items and waste according to relevant regulations.

Measures to Prevent Secondary Accidents Inform relevant organizations immediately to prevent further accidents and

expansion.

Remove nearby potential ignition sources immediately and prepare fire

extinguishing media.

Do not walk on the released material unnecessarily.

7. Handling and Storage

Handling

Technical Measures : Amounts larger than the designated amount must be handled in a factory, a

storage facility, or a laboratory in compliance with the standards required by the

relevant regulations.

Connect the equipment to ground and use explosion-proof electric appliances as

an anti-static measure.

Do not use high-temperature objects, sparks and fire nearby. - No smoking.

Take engineering measures and use protective equipment as described in

Section 8. Exposure Controls/Personal Protection.

Provide local and general ventilation as described in Section 8. Exposure

Controls/Personal Protection.

Precautions for Safe Handling : Do not use things that generate fire, sparks and arcs or high-temperature objects.

Do not spray at an open flame or high-temperature incandescent objects. Use this substance with one's back facing upwind to prevent it from being

blown back on the user.

The container may rupture if stored in a high-temperature place.

Avoid contact, inhalation, or ingestion. Do not get in eyes. Wash hands

thoroughly after handling.

Avoid contact with combustibles and oxidizing agents.

Storage

Proper Storage Conditions : Store in a cool, well-ventilated place, away from direct sunlight. Keep

containers sealed.

May leak or spray out if containers get rusty. Avoid storing it in a humid spot.

Store away from fire and heat sources.

Do not store where the temperature exceeds 40°C.

Use explosion-proof grounded electric appliances if using them in the storage

area.

Store away from combustibles and oxidizing agents.

Store locked up.

Safe Packaging Materials : Use containers regulated by the High Pressure Gas Safety Act and other

regulations.

8. Exposure Controls/Personal Protection

Control Levels : Total dust 3.0 mg/m³

Permissible Exposure Levels

Japan Society for

Iron oxide...inhalant dust 1 mg/m³, Total dust 4 mg/m³

Occupational Health (2015 version)

Butane...500 ppm, 1,200 mg/m³

ACGIH TLV-TWA

(2008 Version) Iron oxide...5 mg, Fe/m³, propane...1,000 ppm, butane...1,000 ppm

In an indoor, inadequately ventilated workplace, provide local or general **Engineering Measures**

ventilation equipment. Install a face-washer and safety shower.

Do not put high-temperature and ignition sources near where this material is

handled.

Protective Equipment Wear the following protective equipment as needed:

Respiratory System

Organic gas masks, air-supplied respirators, breathing equipment, etc.

Protection **Hand Protection**

Protective gloves (solvent resistant, impermeable)

Eye Protection Eye protection, face protection.

Skin and Body Protection

Oil-resistant (impermeable, anti-static) apron

(anti-static) protective wear, electrically conductive boots, etc.

9. **Physical and Chemical Properties**

	Contained liquid	Spraying agent (LPG)
Physical state	Liquid	Under atmospheric pressure: gas, in pressurized container: liquid
Color	Colorless and transparent	Colorless and transparent
Odor	Almost none	odorless
Melting point/ freezing point	-60°C or less (pour point)	-187.7138.4°C
Boiling point or initial boiling point and boiling range	210–250°C	-42.10.5°C
Flammability	Flammable	Flammable
Lower and upper explosion limit / flammability limit	0.6–6.5%	1.8–9.5vol%
Flash point	90°C or higher (open cup)	-104.473.8°C
Auto-ignition temperature	approx. 350°C	405–550°C
Decomposition temperature	No data available	No data available
рН	No data available	No data available
Kinematic viscosity	No data available	No data available
Solubility	Water insoluble, poorly soluble in alcohol Readily soluble in toluene and hexane	Slightly soluble in water
Partition coefficient n-octanol/water (log value)	No data available	No data available

Vapor pressure	No data available	0.278–1.275 MPa (40°C)
Density and/or relative density	0.79 (15/4°C)	0.539 (20°C)
Relative vapor density	No data available	1.895–2.538 kg/m³ (1 MPa 15.6°C)
Particle characteristics	14μm (8-20μm)	No data available

10. Stability and Reactivity

Chemical Reactivity and

Stability

: May rupture at 40°C or higher

Internal pressure at ambient temperature: approx. 0.35 MPa

May catch fire and explode by electrostatic discharge

Possibility of Hazardous

Reactions

: May rupture by heat and impact.

A flammable liquefied gas and readily forms an explosive gas when mixed with

air.

Conditions to Avoid : Storage in hot, humid spots and usage near fire.

Incompatible Materials
Hazardous Decomposition

Products

No data available
No data available

11. Toxicological Information

Acute Toxicity (oral) : $LD_{50} \ge 20 \text{ g/kg (mouse)}$: isoparaffin

Acute toxicity (dermal) : No data available

Acute Toxicity (inhalation) : gas...

 $LC_{50} > 55,000$ ppm/2 h (guinea pig): propane $LC_{50} > 38,890$ ppm/4 h (guinea pig): propane $LC_{50} > 277,374$ ppm/4 h (rat): n-butane

Skin Corrosion and Skin

Irritation : No data available

Serious Eye Damage or Eye

Irritation

: No data available

Respiratory Sensitization or

Skin Sensitization

: Respiratory sensitization: No data available

Skin sensitization: No data available

Germ Cell Mutagenicity : No data available
Carcinogenicity : No data available
Reproductive Toxicity : No data available

Specific Target Organ

Toxicity, Single Exposure : Description in ACGIH: propane "Anesthetic to humans"

Description in ACGIH and Japan Society for Occupational Health

recommendation: n-butane "Anesthetic or central nervous system depressant in

humans by high-concentration inhalation"

Specific Target Organ

Toxicity, Repeated Exposure : No data available
Aspiration Hazard : No data available

12. Ecological Information

Ecotoxicity : No data available
Persistency/Degradability : No data available
Bioaccumulative Potential : No data available
Mobility in Soil : No data available

Hazardous to the Ozone

Layer : No data available

13. Disposal Considerations

Dispose of after complete degassing.

Have contents/container disposed of by an industrial waste disposal contractor licensed by the prefectural governor.

Dispose of or have waste generated from effluent treatment or incineration disposed of by a waste disposal contractor in accordance with the Waste Management and Public Cleansing Act and other related laws.

14. Transport information

UN Hazard Class : 2.1 UN No. : 1950 Follow other related laws and regulations.

15. Regulatory Information

Comply with the applicable laws and regulations regarding this product in each country/region.

16. Other Information

This Safety Data Sheet was prepared in accordance with JIS Z 7253:2019 to provide users of this product with reference information to ensure safe handling. Users are responsible for taking appropriate measures for individual handling conditions with reference to this SDS.

This SDS does not represent any guarantee of safety.

Major references

Safety Data Sheets (SDS) provided by raw material manufacturers

Japanese Standards Association (JIS) JIS Z 7253:2019 "Hazard communication of chemicals based on GHS"

NITE Chemical Risk Information Platform (CHRIP)